

900-D North Macon Street
Baltimore, MD 21205, USA

U.S. Tel. 410-342-3820 U.S. Fax 410-342-7324


Email: main@newvistacorp.com

Website: www.newvistacorp.com

CATALOG PUBLICATION

NEW VISTA PLS-25 DEBURRING UNIT

— A variable-rpm Deburring Unit with servo advance —



PLS DEBURRING UNIT FEATURES:

- ◆ Supplied with Touchscreen HMI.
- ◆ Variable rpm (var. freq.) AC drive: 100 – 2000 rpm, 230/460 vac.
- ◆ Servo-driven feed-advance. Feed rates set/selected from touchscreen supplied.
- ◆ Feed capacities to match customer's applications.
- ◆ Built for continuous service in automated systems.
- ◆ Available with a variety of deburring tools.
- ◆ Capacity: Hole sizes from Ø6mm (1/4 inch) through Ø26mm (1-1/32 inch).
- ◆ Gear-driven, with twin set of duplex (angular-contact) ball bearings.
- ◆ Used to deburr both ends (both sides) of bores and holes — in a single pass.
- ◆ Just a few seconds to deburr any hole.
- ◆ Hole roundness and hole alignment are not critical.
- ◆ Will work with flimsy stampings as well as machined parts.
- ◆ See long reach videos on New Vista's website: www.newvistacorp.com.